

THE DOW CHEMICAL COMPANY SALES SPECIFICATION

Date Printed: 2022-01-05

Effective Date: 2020-07-10 **Supersedes Date:** 2019-06-28

Name: DOWSIL™ 799 Silicone Glass and Metal Building Sealant Clear

Specification Number: 000000860885

Shelf Life

Container Type	Conditions of	Conditions of	Shelf	Deterioration
	Handling	Storage	Life	Characteristics
All Approved Packaging		Store BELOW 32C/90F	720 Days	

Final Testing Requirements

Test and Test Condition	Limit	Unit	Method	Note
Appearance, smooth uniform paste, so graininess acceptable	ome Pass		CTM0176	
Durometer, 7d/RT	25 Min	ShoreA	CTM0099	
Tensile, 7d/RT	175 Min	psi	CTM0137A	
Elongation, 7d/RT	300 Min	%	CTM0137A	
Lap Shear Tensile - Glass/Alum, 10d/RT	Γ 100 Min	lb/in2	CTM0243	
Lap Shear Tensile - G Steel/Norylplastic	c, 100 Min	lb/in2	CTM0243	
Test Frequency: a	udit once per year			

External Notes

1 Dow Chemical warrants that the above designated material conforms to the listed sales specifications even though there may be no value reported.

Test Item Limits

Durometer (7d/RT) >= 25 Shore A

Tensile (7d/RT) >= 175 psi

Elongation (7d/RT) >= 300 %

Lap Shear Tensile - Glass/Aluminum (10d/RT) >= 100 psi

Lap Shear Tensile - Galv St/Norylplastic (10d/RT) >= 100 psi

[®] ™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

THE DOW CHEMICAL COMPANY SALES SPECIFICATION

Name: DOWSIL™ 799 Silicone Glass and Metal Building Sealant Clear

Specification Number: 000000860885 **Effective Date:** 2020-07-10

READ PRECAUTIONARY INFORMATION AND MATERIAL SAFETY SHEETS. THIS PRODUCT IS SHIPPED IN COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS REGARDING CLASSIFICATION, PACKAGING, SHIPPING AND LABELING.