

Concrete Stain Sealer VOC

CSSV G001 * 1 gal (3.8 L) Can

CSSV G005 * 5 gal (18.9 L) Pail

Pigmented, low-VOC, solvent-based, acrylic concrete stain and sealer.

* See Increte Standard Color Chart on pg. 27 for 3-digit color codes
For clear, tintable base use color code 000

CONCRETE FINISHING EFFECTS & AIDS

EZ Expose

CSUC G001 000 Grade 5: 1 gal (3.8 L) Unit

CSUC G005 000 Grade 5: 5 gal (18.9 L) Unit

CSUF G001 000 Grade 25: 1 gal (3.8 L) Unit

CSUF G005 000 Grade 25: 5 gal (18.9 L) Unit

CSUK G001 000 Grade 100: 1 gal (3.8 L) Unit

CSUK G005 000 Grade 100: 5 gal (18.9 L) Unit

CSUT G001 000 Grade 200: 1 gal (3.8 L) Unit

CSUT G005 000 Grade 200: 5 gal (18.9 L) Unit

Water-based concrete surface retarder used to create an exposed aggregate finish on freshly-poured concrete.

Eucobar

028 95 1 gal (3.8 L) Jug

028 05 5 gal (18.9 L) Pail

028 55 55 gal (208 L) Drum

Concentrated evaporation retardant and finishing aid, holds in surface moisture, helps prevent plastic shrinkage cracking.

Cement Retarder

CCRT G001 000 1 gal (3.8 L) Container

CCRT G001 000 5 gal (18.9 L) Container

Easy-to-use, water-based additive that prolongs the setting time for cement-based products, including concrete and cementitious overlays.

CONCRETE OVERLAYS

SELF-LEVELING OVERLAYS

Level Top PC-AGG

407A 50 Gray: 50 lb (22.7 kg) Bag

407W3 50 White: 50 lb (22.7 kg) Bag

407S50 Colors: 50 lb (22.7 kg) Bag

Polishable self-leveling overlayment with natural aggregate.

Level Top Polish

CLHS P050 355 50 lb (22.7 kg) Bag

CLHS P050S Colors: 50 lb (22.7 kg) Bag

Polishable self-leveling overlayment.

Level Top Stain

CLTO P050 355 50 lb (22.7 kg) Bag

Self-leveling re-surfacing compound that can be integrally colored, stained or dyed.

STAMPABLE OVERLAYS

Thin-Crete Grout

CTCG P050 * 50 lb (22.7 kg) Bag

Stampable single-component, polymer-modified, cementitious overlay.

* See Increte Standard Color Chart on pg. 27 for 3-digit color codes
For tintable base use color code 000

SPRAYABLE OVERLAYS

Spray-Deck/Texture-Crete Grout

CSDG P050 355 Gray: 50 lb (22.7 kg) Bag

CSDG P050 970 White: 50 lb (22.7 kg) Bag

A two-component, polymer modified cementitious grout that is mixed with Spray Deck Resin to produce a textured finish.

Spray-Deck Single Component Grout

CSCG P050 355 Gray: 50 lb (22.7 kg) Bag

CSCG P050 970 White: 50 lb (22.7 kg) Bag

CSCF P050 970 White (Fine): 50 lb (22.7 kg) Bag

Pre-blended cementitious coating uniquely formulated with fine aggregate that produces a textured finish.

Spray-Deck Resin

CSDR G001 000 1 gal (3.8 L) Unit

CSDR G005 000 5 gal (18.9 L) Unit

Specialty-formulated acrylic that modifies cementitious materials, including overlays and masonry, specifically engineered for use with Spray Deck Grout.

Renovate

CREK P025 970 25 lb (11.3 kg) Kit

Two-component, polymer-modified cementitious coating used to resurface concrete.

TROWEL-APPLIED OVERLAYS

Euco Re-Cover

150R 40 Gray: 40 lb (18 kg) Bag

CMIC P040 970 White: 40 lb (18 kg) Bag

Polymer modified, fiber-reinforced concrete resurfacing mortar.

OVERLAY BONDING AGENTS

Tammsweld

THHWJ01 6/1 gal (3.8 L) Jugs

THHWPO5 5 gal (18.9 L) Pail

Rewettable liquid bonding agent and polymer modifier for concrete and cement mortars.

Eucoweld 2.0

L6202 95 6/1 gal (3.8 L) Jugs

L6202 05 5 gal (18.9 L) Pail

Liquid latex bonding agent for cement-based repairs and toppings.

High Performance Epoxy Primer Express

CEPE G003 000 3 gal (11.4 L) Kit

Rapid turnaround epoxy primer for Level Top overlay systems.