





Roofing Nail with Neoprene Washer 

For aluminum roofing and fiberglass roofing. Neoprene washer provides an effective waterproof seal.

Roofing Nail		Aluminum Ring Shank With Neoprene Washer		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1-3/4"	9	3/8"	260	134ANEO


Shingle Nail 

For attaching thin sidewall shingles. Sturdy slim shank prevents splitting.**

Shingle Nail		Hot Dipped Galvanized Smooth Shank			
<small>Approved for use with 40% of treated lumber</small>		Gauge	Head Size	Approx. Count Per Pound	SKU
Size					
1-1/4"	3D	13	1/4"	425	3HGSHG
1-3/8"	3-1/2D	12-1/2	9/32"	345	312HGSHG
1-1/2"	4D	12	9/32"	271	4HGSHG

* All Grip-Rite hot dipped galvanized fasteners meet ASTM A-153 requirements and can be used with treated lumber.

** Grip-Rite stainless steel nails or screws should be used for all redwood and cedar projects, for marine projects, and within 5 miles of coastline.

Roofing Nail 


For attaching copper flashing and other decorative copper roofing elements. Large head for greater holding power. Smooth shank for ease of penetration.

Roofing Nail		Copper Smooth Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
3/4"	11	3/8"	295	P34CPRFG
1"	11	3/8"	229	P1CPRFG
1-1/4"	11	3/8"	187	P114CPRFG
1-1/2"	11	3/8"	155	P112CPRFG
1-3/4"	11	3/8"	139	P134CPRFG
2"	11	3/8"	84	P2CPRFG
2-1/2"	11	3/8"	70	P212CPRFG

Lead Head Nail 

For metal roofing applications. Lead head flattens out with impact, creating a seal against the metal roof.

Lead Head Nail		Bright Smooth Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1-3/4"	10	3/8"	88	134LH
2-1/2"	10	3/8"	71	212LH

Tile Nail 

For use with clay roofing tiles. Long shank is sturdy enough to insert through the predrilled hole in Spanish tile, while the oversized head prevents the nail from going all the way through the hole.

Tile Nail		Electrogalvanized Smooth Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
4"	9	15/32"	50	4EGTL
4-1/2"	9	15/32"	45	412EGTL
5"	9	15/32"	38	5EGTL
5-1/2"	8	15/32"	36	512EGTL
6"	8	15/32"	32	6EGTL
8"	8	15/32"	28	8EGTL