

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/23/2015

Revision date: 8/29/2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SOPRASEAL LM 202 VP and SOPRASEAL LM 203

1.2. Relevant identified uses of the substance or mixture and uses advised against

One-component spray applied vapor-permeable air barrier membrane used in wall construction.

1.3. Details of the supplier of the safety data sheet

Manufacturer:
SOPREMA USA
310 Quadral Dr.
Wadsworth, OH 44281
Tel: 1-800-356-3521

Distributors:
SOPREMA Canada
1675 Haggerty Street
Drummondville (Quebec) J2C 5P7
Tel: 1-819-478-8163

SOPREMA Canada
44955 Yale Road West
Chilliwack (BC) V2R 4H3
CANADA
Tel: 1-604-793-7100

SOPREMA USA
12251 Seaway Road
Gulfport (Mississippi) 39507
UNITED STATES
Tel: 1-228-701-1900

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
Muta.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity
STOT RE	1 (by inhalation)	Specific target organ toxicity – repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H317 - May cause an allergic skin reaction
H351 - Suspected of causing cancer

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US)	H340 - May cause genetic defects
	H360 - May damage fertility. May damage the unborn child.
	H372 - Causes damage to organs (lung) through prolonged or repeated exposure (Inhalation)
	H402 - Harmful to aquatic life
	H412 - Harmful to aquatic life with long lasting effects
	: P201 - Obtain special instructions before use
	P202 - Do not handle until all safety precautions have been read and understood
	P270 - Do not eat, drink or smoke when using this product
	P273 - Avoid release to the environment
	P280 - Wear nitrile gloves and safety glasses
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
	P362+P364 - Take off contaminated clothing and wash it before reuse
	P405 - Store locked up
	P501 - Dispose of container in accordance with local, regional or national regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Crystalline silica	(CAS No) 14808-60-7	>=25 - 50
Limestone	(CAS No) 1317-65-3	>=10 - 20
Kieselguhr, soda ash flux-calcined	(CAS No) 68855-54-9	>=1 - 3
Titanium dioxide	(CAS No) 13463-67-7	>=1 - 3
Ethanol, 2-(hydroxymethylamino)	(CAS No) 34375-28-5	>=0.1-0.2
diuron	(CAS No) 330-54-1	>=0 - 0.1
1,2-benzisothiazol-3(2H)-one	(CAS No) 2634-33-5	>=0 - 0.1
Carbamic acid, butyl-, 3-iodo-2-propynyl ester	(CAS No) 55406-53-6	>=0 - 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see ... on this label). Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause cancer by inhalation.
------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 R
USA OSHA	Remark (US OSHA)	(3) See Table Z-3.
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
USA ACGIH	Remark (ACGIH)	LRT irr; A3
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

diuron (330-54-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA ACGIH	Remark (ACGIH)	URT irr

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear nitrile gloves
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: pink
Odor	: No data available on odour
Odor threshold	: No data available
pH	: ≈ 8 - 9.5
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific Gravity	: No data available
Density	: ≈ 1.47 – 1.54 g/cm ³
Solubility	: Water: miscible
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 17.0 g/L - SOPRASEAL LM 202 VP 21.0 g/L - SOPRASEAL LM 203
-------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures.

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value)

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	1020 mg/kg (Rat; Literature study)
ATE US (oral)	1020.00000000 mg/kg body weight

3-iodo-2-propynyl butylcarbamate (55406-53-6)	
LD50 oral rat	300-500,Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Experimental value
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	0.67 mg/l/4h (Rat; Experimental value)
ATE US (oral)	500.00000000 mg/kg body weight
ATE US (gases)	700.00000000 ppmV/4h
ATE US (vapors)	0.67000000 mg/l/4h
ATE US (dust, mist)	0.67000000 mg/l/4h

Skin corrosion/irritation : Not classified
pH: ≈ 8 - 9.5

Serious eye damage/irritation : Not classified
pH: ≈ 8 - 9.5

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer.

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause an allergic skin reaction. May cause cancer by inhalation.

SECTION 12: Ecological information

12.1. Toxicity

Titanium dioxide (13463-67-7)	
LC50 fish 1	> 1000 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	< 1000 mg/l (432 h; Daphnia magna; Static system)

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium dioxide (13463-67-7)	
LC50 fish 2	> 1 g/l (96 h; Leuciscus idus)
EC50 Daphnia 2	< 500 mg/l (720 h; Daphnia magna; Static system)
Threshold limit algae 1	61 mg/l (72 h; Pseudokirchneriella subcapitata)

3-iodo-2-propynyl butylcarbamate (55406-53-6)	
LC50 fish 2	0.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system)
EC50 Daphnia 2	0.16 mg/l (EC50; EPA OPP 72-2; 48 h; Daphnia magna; Flow-through system)
Threshold limit algae 1	0.022 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system)

12.2. Persistence and degradability

SOPRASEAL LM 202 VP	
Persistence and degradability	Not established.

SOPRASEAL LM 203	
Persistence and degradability	Not established.

Quartz (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable. Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Titanium dioxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable. Low potential for mobility in soil. Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Persistence and degradability	Biodegradable in water. No (test) data on mobility of the substance available. Not established.

3-iodo-2-propynyl butylcarbamate (55406-53-6)	
Persistence and degradability	Not readily biodegradable in water. Inherently biodegradable. Low potential for adsorption in soil. Not established.
Chemical oxygen demand (COD)	1.15 g O ₂ /g substance

12.3. Bioaccumulative potential

SOPRASEAL LM 202 VP	
Bioaccumulative potential	Not established.

SOPRASEAL LM 203	
Bioaccumulative potential	Not established.

Quartz (14808-60-7)	
Log Pow	Not applicable
Bioaccumulative potential	No bioaccumulation data available. Not established.

Titanium dioxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative. Not established.

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Log Pow	1.3 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

3-iodo-2-propynyl butylcarbamate (55406-53-6)	
BCF fish 1	3.3 - 4.5 (BCF)
Log Pow	2.81 (Literature; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3-iodo-2-propynyl butylcarbamate (55406-53-6)

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
---------------------------	---

12.4. Mobility in soil

3-iodo-2-propynyl butylcarbamate (55406-53-6)

Surface tension	0.0691 N/m (158 mg/l)
Log Koc	Koc,PCKOCWIN v1.66; 198.1; Calculated value

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of container in accordance with local, regional or national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

Transport document description :

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Registration status

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories)

Refer to SDS section 2 for GHS hazard classes applicable for this product.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

SOPRASEAL LM 202 VP and SOPRASEAL LM 203

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



WARNING: This product can expose you to 4-Vinylcyclohexane which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

State RTK	CAS Number	Chemical Name
NJ	1317-65-3	Limestone
	13463-67-7	Titanium dioxide
	14808-60-7	Quartz
	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
PA	1317-65-3	Limestone
	13463-67-7	Titanium dioxide
	68855-54-9	Kieselguhr, soda ash flux-calcined
	14808-60-7	Quartz

SECTION 16: Other information

Revision date : 8/29/2018
Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012) - Custom

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/86-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.