

FAST-SETTING SELF-LEVELING FLOOR RESURFACER & SELF-LEVELING FLOOR RESURFACER

Self-finishing interior floor topping and underlayment specially formulated to produce a smooth surface ready for the installation of ceramic tile, resilient flooring or other finishes. No troweling required. **Use for:**

- Resurfacing existing concrete floors with damaged finishes
- Over new concrete floors & pre-cast slabs w/unacceptable finishes

Fast-Setting formula exceeds: 1,800 psi (12.4 MPa) in 24 hours
4,000 psi (27.6 MPa) in 7 days
5,500 psi (37.9 MPa) in 28 days.

Regular formula exceeds: 1,000 psi (6.9 MPa) in 7 days
2,000 psi (13.8 MPa) in 28 days.



Item No.	Package Size	Metric	Quantity
Fast-Setting			
1249-51	50 lb. bag	22.7 kg	64/pallet
Regular			
1249-50	50 lb. bag	22.7 kg	64/pallet

THIN SET SANDED

A Portland cement based thin set for setting absorptive & non-absorptive tile on walls and floors. Addition of Acrylic Fortifier is recommended.

Apply over:

- Concrete
- Concrete block
- Cementitious backer board
- Wall board
- Portland cement plaster
- Plywood expanded metal lath

Meets the requirements of ANSI A 118-1



Item No.	Package Size	Metric	Quantity
1547-50	50 lb. bag	22.7 kg	63/pallet

THIN SET SANDED - WHITE

A white Portland cement based thin set for setting absorptive & non-absorptive tile on walls and floors. Addition of Acrylic Fortifier is recommended.

Apply over:

- Concrete
- Concrete block
- Cementitious backer board
- Wall board
- Portland cement plaster
- Plywood expanded metal lath

Meets the requirements of ANSI A 118-1



Item No.	Package Size	Metric	Quantity
1547-51	50 lb. bag	22.7 kg	63/pallet

MULTI-PURPOSE THIN SET

A polymer modified, Portland cement based thin set used for setting ceramic tile and natural stone such as marble or granite and saltillo tile on walls and floors. Requires no additional latex or fortifiers. Available in gray and white.

Apply over:

- Plywood
- Cementitious backer units
- Portland cement plaster
- Concrete
- Concrete block
- Wall boards

Meets the requirements of ANSI A 118-1 and ANSI A 118.4.



Item No.	Package Size	Metric	Quantity
Gray			
1550-49	50 lb. bag	22.7 kg	63/pallet
White			
1550-50	50 lb. bag	22.7 kg	63/pallet

FLOOR MUD

Portland cement based underlayment mortar designed for leveling travertine, slate and marble floor tile, and for shower pan applications



Item No.	Package Size	Quantity
1548-81	60 lb. bag	56/pallet
1548-82	80 lb. bag	42/pallet

WALL FLOAT

Portland cement based leveling mortar for vertical applications of tile, marble and brick veneer. Addition of Acrylic Fortifier or Concrete Bonding Adhesive is recommended.



Item No.	Package Size	Quantity
153-50	50 lb. bag	65/pallet
153-76	75 lb. bag	48/pallet