

COLPHENE®

LIQUID MEMBRANE

COLPHENE®
LIQUID MEMBRANE
PRODUCT # A191

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

COLPHENE® Liquid Membrane is a two component, elastomeric, solvent-free, cold applied material used in conjunction with a variety of waterproofing membranes. COLPHENE® Liquid Membrane is designed to be used as an adhesive to seal end-laps and/or reinforcement at penetrations and membrane terminations.

STORAGE

Keep temperature of cartridges between 65-85° F (18-29°C) 24 hours prior to use. Do not store in direct sunlight or high temperatures exceeding 90° F (32°C).

APPLICATION

COLPHENE Liquid Membrane is packaged in cartridges. It is applied via pneumatic/manual cartridge applicator. Refer to the SOPREMA specifications and installation instructions for additional application guidelines.

QUICK FACTS

QUANTITY (L)	QUANTITY (cartridges)	STORAGE TEMP (°F)	COVERAGE (lin ft)
1.5 per cartridge	4 per case	65-85 (18-29°C)	100-125 ¹ per cartridge

¹ Coverage assumes 1/2" to 3/4" wide ribbon application.



www.soprema.us
310 Quadral Drive, Wadsworth, Ohio 44281
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PDS10056 - REV. 000917