

### Product Description

A series of high-density polyethylene sheets designed for membrane protection, as well as various barrier applications.

### Basic Uses

HDPE-20 Protective Vapor and Root Barrier: A 20-mil sheet that not only serves as a protection course but also acts as a vapor barrier in waterproofing applications.

### Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

### Packaging

4' x 100' (1.2 x 30.3 m) roll

### Storage

Store out of direct sunlight. Vertical storage recommended.

### Limitations

- Not for use beneath sand-set vehicular pavers.

### Installation

Tremco HDPE Protective Barriers are installed over a cured waterproofing membrane to prevent damage to the membrane. When installed, all seams should be either heat welded, taped with Tremco JT Tape or Permanent Seam Tape depending upon application. Termination should occur with the Tremco Paraterm Bar at the edge of the waterproofing membrane. Please consult your local Tremco Representative for further details, specific to your application.

### Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	HDPE-20
Thickness	20 mils (0.5 mm)
Puncture Resistance	95 lbs.
Weight	40 lbs.
Dimension	4' x 100' (1.2 x 30.3 m)

0916/TDDS-BG



### Tremco Commercial Sealants & Waterproofing

3735 Green Rd  
Beachwood OH 44122  
216.292.5000 / 800.321.7906

1451 Jacobson Ave  
Ashland OH 44805  
419.289.2050 / 800.321.6357

220 Wicksteed Ave  
Toronto ON M4H1G7  
416.421.3300 / 800.363.3213

1445 Rue de Coulomb  
Boucherville QC J4B 7L8  
514.521.9555