



DRYTEK® MOISTURE VAPOUR BARRIER



Designed for use as a primer over concrete substrates exhibiting elevated moisture vapour emission rates, DRYTEK® MOISTURE VAPOUR BARRIER may be used over damp concrete or new/green concrete that is only 5 days old. This barrier can be incorporated as a primer within any SPARTACOTE® floor coating system or as an underlayment below other types of commercial flooring systems. DRYTEK MOISTURE VAPOUR BARRIER exceeds ASTM F3010 standard with a perm rating of 0.052 grains/h/ft²/in. Hg (3 ng/h • m² • Pa) at only 12 mil thickness.

Code	Description
4151-0003-2	<p>DRYTEK® MOISTURE VAPOUR BARRIER</p> <p>Mini Unit Kit*: 9.1 L</p> <p>Part A: 2.3 L packaged in a steel pail</p> <p>Part B: 6.1 L packaged in a steel pail</p> 
4151-0006-2	<p>DRYTEK MOISTURE VAPOUR BARRIER</p> <p>Full Unit Kit*: 24.6 L</p> <p>Part A: 8.3 L packaged in a steel pail</p> <p>Part B: 16.3 L packaged in a steel pail</p> 

*DRYTEK® MOISTURE VAPOUR BARRIER is a kit of two pails. Individual pails (Part A or Part B) cannot be purchased separately, and cannot be returned separately.



SPARTACOTE® SURFACE BUILD 110™

1:1 mix ratio. Two-component, 100% solids, self-leveling epoxy primer. Available in a 7.6 L kit or 18.9 L pails.

Code	Description
<p>Clear: 9210-0002-2</p> <p>Light Grey: 9218-0002-7</p> <p>Sand Beige: 9219-0002-12</p>	<p>SPARTACOTE® SURFACE BUILD 110™</p> <p>7.6 L box kit contains:</p> <p>Part A: 3.8 L</p> <p>Part B: 3.8 L</p> 
<p>Part A: Clear: 9226-0005-2</p> <p>Part B: Clear: 9228-0005-2</p>	<p>SPARTACOTE SURFACE BUILD 110</p> <p>Part A: 18.9 L</p> <p>Part B: 18.9 L</p> 


SPARTACOTE® SURFACE BUILD 150™

SPARTACOTE® SURFACE BUILD 150™ is a high quality, two-component, self leveling, 100% solids epoxy coating. For use as a build coat for thick mil coating systems. 2:1 (A:B) mix ratio. Available in 7.6 L Part A and 3.8 L Part B Clear. Also available: 18.9 L Part A and 18.9 L Part B.

Code	Description
<p>Part A: 9230-0002-2</p> <p>Part B: 9231-0001-2</p>	<p>SPARTACOTE® SURFACE BUILD 150™</p> <p>Part A: 7.6 L in 11.3 L pail</p> <p>Part B: 3.7 L in pail</p> 
<p>Part A: 9233-0005-2</p> <p>Part B: 9234-0005-2</p>	<p>SPARTACOTE SURFACE BUILD 150</p> <p>Part A: 18.9 L - two units required</p> <p>Part B: 18.9 L</p> 

SPARTACOTE WB EPOXY PRIMER™

Fast-drying, 40% solids, water-based epoxy primer. Available in clear finish or 3 colours, SPARTACOTE® WB EPOXY PRIMER™ is used as a primer coating within indoor applications requiring low VOC emissions and low odour. Mix Ratio: 3:2 (A:B).

Code	Description
9201-0003-2	<p>SPARTACOTE WB EPOXY PRIMER™</p> <p>Part A: 5.7 L in 11.4 L pail</p> 
<p>Clear: 9202-0001-2</p> <p>Sand Beige: 9203-0001-12</p> <p>Light Grey: 9204-0001-7</p> <p>Black: 9205-0001-3</p>	<p>SPARTACOTE WB EPOXY PRIMER</p> <p>Part B: 3.8 L pail</p> 