

# GMAX IRONMAN SERIES

## UNMATCHED DURABILITY



IronMan Series sprayers are designed and built to handle the most brutal and demanding conditions—typically found on large commercial and industrial jobsites.



### THE LONGEST LIFE EVER

#### New Endurance Vortex MaxLife Extreme Piston Pump (PATENTED)

Breakthrough Vortex Rotating Rod Technology Keeps You Spraying:

- Oversized passages for high-velocity flow to rotate rod for even wear
- 6X more gallons sprayed between repacks. Extreme rod extends pump rod life by 3X
- Graco exclusive abrasion-resistance composite delivers the most durable wear surface (PATENTED)
- Repack pump in minutes with new QuikPak cartridge repair system



### ELIMINATE COSTLY DOWNTIME

#### ProConnect 2 One-Part Pump Replacement System (PATENTED)

- Pump swaps in 1 minute or less—no tools, pins, or parts to lose



### NEVER HAVE A FLAT AGAIN

#### Flat Proof Tires

- No tire puncturing from nails, screws, or any sharp debris



### IMPROVED FILTRATION

#### Crushproof Inlet Strainer

- Stands up to harsh impacts to maintain filtering and flow



### EASY-TO-READ PERFORMANCE

#### LED Display

- Displays pressure, gallon counter, and diagnostics



GMAX II 7900 IronMan 17E838

### IronMan Series sprayers also include all Standard Series features:

- SmartControl 3.0
- Precision Advantage Drive
- Honda Engine
- Easy Out Pump Filter
- Heavy-Duty Prime Valve
- Rugged, Durable Cart Design
- **NEW** Contractor PC Gun



Ready to Spray: Complete with Spray Gun, 50' Blue Max II hose, and RAC X SwitchTip



# HIGH PRODUCTION PERFORMANCE

## GH HYDRAULIC TECHNOLOGY

Graco's powerful GH hydraulic units are built for high-production contractors spraying a wide range of thick materials on large commercial jobs.

Hydraulic sprayers use a gas engine or an electric motor to power a hydraulic system that drives the fluid pump.



### LESS MAINTENANCE

#### Innovative component designs keep you spraying

- Inside-out filter flow and oversized filter surface prevent filter collapsing
- High-pressure form-fitted hydraulic fittings and lines eliminate leaks
- Efficiently cooled hydraulic fluid only needs changing once per year



### INCREDIBLE DURABILITY

#### Built to withstand the most extreme abuse

- Exclusive Crushproof Inlet Strainer (ProContractor Series Only)
- Shroud support protects belt from jobsite damage
- Durable steel frame withstands rugged environments
- Heavy-duty prime valve withstands high-pressure dumping



### REDUCED DOWNTIME

#### Chromex and MaxLife pumps provide long life between pump repacks

- ProConnect Pump Replacement System
- Pump removal and replacement in minutes (ProContractor Series only)

### BUILT FOR HOW YOU WORK

#### QuikReel Hose Management System

- Increased versatility with flexible material hose
- Deploying and rewinding up to 300 feet of hose in seconds



GH™ 230 Convertible 24W932

GMAX SERIES	IRONMAN	ROOF RIG
GMAX II 5900	17E833	
GMAX II 7900	17E838	17E835



# GMAX GAS AIRLESS SPRAYER SPECIFICATIONS

		GMAX 3400	GMAX II 3900	GMAX II 5900	GMAX II 7900
SPECIFICATIONS	Maximum Tip Size	0.027	0.036	0.043	0.048
	Maximum psi (bar)	3300 (227)	3300 (227)	3300 (227)	3300 (227)
	Maximum gpm (lpm)	0.75 (2.8)	1.25 (4.7)	1.60 (6.0)	2.20 (8.3)
	Honda Engine CC (HP)	120 (4.0)	120 (4.0)	200 (6.5)	200 (6.5)
	Control	SmartControl 3.0	SmartControl 3.0	SmartControl 3.0	SmartControl 3.0
	Weight lb (kg)	89 (41)	109 (50)	139 (64)	146 (67)
	Gun Support (Gas):				
	1 Gun	0.027	0.036	0.043	0.048
	2 Guns	-	0.023	0.029	0.035
	3 Guns	-	-	0.023	0.027
4 Guns	-	-	-	0.023	
Gun Support (Electric):					
1 Gun	N/A	N/A	0.031	N/A	
2 Guns			0.017		



SERIES TYPE		STANDARD	LO-BOY	STANDARD	PROCONTRACTOR	LO-BOY	CONVERTIBLE	STANDARD	PROCONTRACTOR	IRONMAN	LO-BOY	STANDARD	PROCONTRACTOR	IRONMAN
MODEL	Cart Design — Part Number	17E825	17E826	17E827	17E828	17E829	17E830	17E831	17E832	17E833	17E834	17E836	17E837	17E838 Roof Rig—17E835
PUMP	Type	Endurance	Endurance	Endurance	Endurance Vortex	Endurance	Endurance	Endurance	Endurance Vortex	Endurance Vortex	Endurance Vortex	Endurance	Endurance Vortex	Endurance Vortex
	Rod	Chromex	Chromex	Chromex	MaxLife	Chromex	Chromex	Chromex	MaxLife	MaxLife EXTREME	MaxLife	MaxLife	MaxLife	MaxLife EXTREME
	Sleeve	Hardened SST	Hardened SST	Hardened SST	MaxLife	Hardened SST	Hardened SST	Hardened SST	MaxLife	MaxLife	MaxLife	MaxLife	MaxLife	MaxLife
	Removal	QuikChange	ProConnect 2	QuikChange	ProConnect 2	ProConnect 2	QuikChange	QuikChange	ProConnect 2	ProConnect 2	ProConnect 2	QuikChange	ProConnect 2	ProConnect 2
FEATURES	<b>NEW!</b> Endurance Pump	●	●	●	● Vortex	●	●	●	● Vortex	● Vortex	● Vortex	●	● Vortex	● Vortex
	Honda Engine	●	●	●	●	●	●	●	●	●	●	●	●	●
	Advantage Drive	●	●	●	●	●	●	●	●	●	●	●	●	●
	Easy Out	●	●	●	●	●	●	●	●	●	●	●	●	●
	SmartControl 3.0	●	●	●	●	●	●	●	●	●	●	●	●	●
	LED Display				●				●	●			●	●
	WatchDog				●				●	●			●	●
	QuikReel				●				●	●			●	●
	ProConnect 2		●		●	●			●	●	●		●	●
	<b>NEW!</b> Flat Proof Tires													●
<b>NEW!</b> Crushproof Inlet Strainer				●					●	●			●	●
<b>NEW!</b> Contractor PC Gun	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Tip	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517	RAC X LTX 517
Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless AND 1/4 in x 3 ft (6.4 mm x 0.9 m) BlueMax II Whip Hose	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless AND 1/4 in x 3 ft (6.4 mm x 0.9 m) BlueMax II Whip Hose	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless AND 1/4 in x 3 ft (6.4 mm x 0.9 m) BlueMax II Whip Hose	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless AND 1/4 in x 3 ft (6.4 mm x 0.9 m) BlueMax II Whip Hose	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless AND 1/4 in x 3 ft (6.4 mm x 0.9 m) BlueMax II Whip Hose	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless AND 1/4 in x 3 ft (6.4 mm x 0.9 m) BlueMax II Whip Hose
WEAR PARTS	Replacement Pump	246428	16X414	16Y598	17H823	16X419	16Y706	16Y706	17H824	17H826	17H825	16X423	17H825	17H827
	QuikPak Repair Kit	18B260	17H838	17H838	17H841	17H839	17H839	17H839	17H842	17H843	17H840	17H840	17H840	17H844
	Rod	249125	16X434	248206	17H876	16X435	248207	248207	17H877	17H879	17H878	249119	17H878	17H880
	Sleeve	-	248209	248209	17H864	248210	248210	248210	257031	257031	249121	249121	249121	249121
	Intake Seat Kits	246429	239922	239922	239922	244199	244199	244199	244199	17H888	240918	240918	240918	17H889
MANUAL	Operation and Parts	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400	3A6400
	Pump	309250	3A6583	3A6584	3A6583	3A6583	3A6584	3A6584	3A6583	3A6583	3A6583	3A6584	3A6583	3A6583