

**L&M™ DEBOND®**

Refer to Data Sheet 175.9  
8-16-354-1892/8-16-354-1134/8-16-354-1132



L&M™ DEBOND® is a non-staining, low VOC, concrete form release for application to all types of concrete forms.

**FEATURES/BENEFITS:**

- Reduces concrete build-up and bugholes
- Non-residual, non-staining
- Effective on all types of forms
- Low odor

**PACKAGING:**

- 1 gal (3.8 L)
- 5 gal (18.9 L)
- 55 gal (208 L)
- 275 gal (1040 L) totes

**L&M DEBOND GOLD**

Refer to Data Sheet 175.8  
8-16-355-1891/8-16-355-1139/8-16-355-1136



L&M DEBOND GOLD is a non-staining, low VOC, concrete form release for application to all types of concrete forms, but especially for use in demanding pre-stress and precast applications.

**FEATURES/BENEFITS:**

- Premium quality release for prestress and precast plants
- Helps eliminate concrete build-up and bugholes
- Non-residual, non-staining
- Low VOC

**PACKAGING:**

- 5 gal (18.9 L)
- 55 gal (208 L)
- 275 gal (1040 L) totes

**APPROXIMATE COVERAGE**

For pipe plants, block plants, paving equipment:  
Coat lightly before each use.

Pre-stress and Precast	1,500-2,000 ft <sup>2</sup> /gal (35-50m <sup>2</sup> /L)
Steel, plastic, fiberglass	800-1,200 ft <sup>2</sup> /gal (20-30 m <sup>2</sup> /L)
Wood and other porous forms	600-800 ft <sup>2</sup> /gal (15-20 m <sup>2</sup> /L)

**APPROXIMATE COVERAGE**

For pipe plants, block plants, paving equipment:  
Coat lightly before each use.

Pre-stress and Precast	1,500-2,000 ft <sup>2</sup> /gal (35-50m <sup>2</sup> /L)
Steel, plastic, fiberglass	800-1,200 ft <sup>2</sup> /gal (20-30 m <sup>2</sup> /L)
Wood and other porous forms	600-800 ft <sup>2</sup> /gal (15-20 m <sup>2</sup> /L)

