



**Premium Building Products  
That Protect**

## Protecto Wrap Detail Tapes

Flooring: AFM 500

Building: PSDS

Building: JS500

Basic Use			
Typical Application	Unreinforced conformable sheet used prior to installing AFM-WM for detailing inside corners, drains, posts, protrusions, and floor-to-wall transitions.	Inside window corner details	Unreinforced conformable sheet used for detailing around protrusions, drains, footings and non-uniform surfaces.
Packaging	6" x 50' Rolls 12" x 50' Rolls	6" x 6" Squares 6" x 50' Rolls	6" x 50' Rolls 12" x 50' Rolls
Technical Properties			
Thickness	30 mil	40 mil	60 mil
Color	Black		
Composition	SBS Modified Rubberized Asphalt		
Elongation (ASTM D412)	500%		
Permeance (ASTM E96B)	0.003 inch-pounds max		
Pliability (ASTM D146)	Pass		
Water Absorption	0.23 max		
Exposure to fungi in soil for 16 weeks (GSA-PBS 07115)	Unaffected		
Resistance to hydrostatic head	150 feet of water		

### Protecto Wrap Company

1955 South Cherokee Street Denver, CO 80223 1-800-759-9727 (303) 777-3001 Fax (303)777-9273 www.protectowrap.com