

SAFETY DATA SHEET

1. Identification			
Product identifier	L&M DURAGROUT		
Other means of identification	None.		
Recommended use	Industrial grout.		
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.		
Manufacturer/Importer/Supplier/	Distributor information		
Company Name Address	LATICRETE International 1 Laticrete Park, N Bethany, CT 06524		
Telephone Contact person Website Emergency phone number	(203)-393-0010 Steve Fine www.laticrete.com Call CHEMTREC day or night USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887		
2. Hazard(s) identification			
Physical hazards	Not classified.		
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 1	
	Sensitization, skin	Category 1	
	Carcinogenicity	Category 1A	
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation	
	Specific target organ toxicity, repeated exposure	Category 2 (lung)	
OSHA defined hazards	Not classified.		
Label elements			
	\vee \vee \vee		
Signal word	Danger		
Hazard statement	Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. May cause damage to organs (lung) through prolonged or repeated exposure.		
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace.		
Response	If exposed or concerned: Get medical advice/a keep comfortable for breathing. If on skin: Was	attention. If inhaled: Remove person to fresh air and sh with plenty of water. If skin irritation or rash	

occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

3. Composition/information on ingredients

Mixtures			
Chemical name		CAS number	%
Silica Sand		14808-60-7	60-65
Portland Cement		65997-15-1	32-38
Calcium aluminate cement		65997-16-2	22-26
Calcium sulfate, anhydrous		14798-04-0	1-3
Composition comments	All concentrations are in percent by weigh percent by volume.	it unless ingredient is a gas. Gas	concentrations are in
4. First-aid measures			
nhalation	Remove victim to fresh air and keep at resident if symptoms develop or persist.	st in a position comfortable for b	eathing. Call a physic
Skin contact	Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.		
ngestion	Rinse mouth. Get medical attention if symptoms occur.		
Most important symptoms/effects, acute and delayed	Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and	I treat symptomatically.	
General information	Ensure that medical personnel are aware protect themselves. IF exposed or concer clothing before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. C	Carbon dioxide (CO2).	
Unsuitable extinguishing media	None known.		
Specific hazards arising from the chemical	During fire, gases hazardous to health ma	ay be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and fu	Ill protective clothing must be wo	orn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not bre	athe fumes.	
General fire hazards	No unusual fire or explosion hazards note	d.	
6. Accidental release mea	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep protective equipment and clothing during material unless wearing appropriate prote	clean-up. Do not touch damaged	containers or spilled

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

Conditions for safe storage, Ke including any incompatibilities

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

PEL PEL 1910.1000)	5 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable fraction.
	5 mg/m3	Respirable fraction.
1910.1000)		·
	15 mg/m3	Total dust.
Туре	Value	Form
TWA	50 mppcf	
TWA	0.3 mg/m3	Total dust.
	0.1 mg/m3	Respirable.
	2.4 mppcf	Respirable.
/alues		
Туре	Value	Form
TWA	10 mg/m3	Inhalable fraction.
TWA	1 mg/m3	Respirable fraction.
TWA	0.025 mg/m3	Respirable fraction.
Chemical Hazards		
Туре	Value	Form
TWA	5 mg/m3	Respirable.
	10 mg/m3	Total
TWA	5 mg/m3	Respirable.
	10 mg/m3	Total
TWA	0.05 mg/m3	Respirable dust.
No biological exposure limits noted for	or the ingredient(s).	
Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		
Wear chemical-resistant, impervious	aloves.	
	-	
	TWA Values Type TWA Good general ventilation (typically 10 should be matched to conditions. If all or other engineering controls to maint exposure limits have not been establic eyewash station. such as personal protective equipm Wear safety glasses with side shields Wear chemical-resistant, impervious	TWA 0.3 mg/m3 0.1 mg/m3 2.4 mppcf /alues Type Value TWA 10 mg/m3 TWA 1 mg/m3 TWA 1 mg/m3 TWA 0.025 mg/m3 Chemical Hazards Type Value TWA 5 mg/m3 No biological exposure limits noted for the ingredient(s). Occupational exposure to nuisance dust (total and respirable) and respinable be monitored and controlled. Good general ventilation (typically 10 air changes per hour) should be should be matched to conditions. If applicable, use process enclosur or other engineering controls to maintain airborne levels below recon exposure limits have not been established, maintain airborne levels to conditione lev

L&M DURAGROUT

Respiratory protection
Thermal hazardsWear a dust mask if dust is generated above exposure limits.General hygiene
considerationsAlways observe good personal hygiene measures, such as washing after handling the material
and before eating, drinking, and/or smoking. Routinely wash work clothing and protective
equipment to remove contaminants. Contaminated work clothing should not be allowed out of the
workplace.

9. Physical and chemical properties

Appearance		
Physical state	Solid.	
Form	Powder.	
Color	Grey.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not available.	
Flash point	Not available.	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or expl	losive limits	
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	2.65	
Solubility(ies)		
Solubility (water)	Insoluble	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Viscosity	Not available.	

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of ex	rposure
Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet cement/mixture may cause burns.

Eye contact	Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.		
Ingestion	Swallowing may cause gastrointestinal irritation.		
Symptoms related to the physical, chemical and toxicological characteristics	Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.		
Information on toxicological effe	ects		
Acute toxicity	May cause respiratory irritation.		
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye damage.		
Respiratory or skin sensitization	n		
Respiratory sensitization	No data available.		
Skin sensitization	May cause an allergic skin reaction.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	e	
Carcinogenicity	May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003)		
IARC Monographs, Overall	Evaluation of Carcinogenicity		
Silica Sand (CAS 14808- NTP Report on Carcinogen	60-7) 1 Carcinogenic to humans.		
Silica Sand (CAS 14808-			
	ed Substances (29 CFR 1910.1001-1050)		
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause respiratory irritation.		
Specific target organ toxicity - repeated exposure	May cause damage to organs (lung) through prolonged or repeated exposure.		
Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.		
Chronic effects	Prolonged or repeated exposure may cause lung injury, including silicosis.		
12. Ecological information	1		
Ecotoxicity	Not expected to be harmful to aquatic organisms.		
Components	Species Test Results		
Calcium sulfate, anhydrous (C	CAS 14798-04-0)		
Aquatic			
Fish	LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours		
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available for this product.		
Mobility in soil	The product is not mobile in soil.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creat potential, endocrine disruption, global warming potential) are expected from this component		

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations. Do not contaminate ponds, waterways or ditches with chemical or used container.

L&M DURAGROUT

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
14. Transport information	
DOT	
Not regulated as dangerous g	oods.
IATA Not regulated as dangerous g	oods
IMDG	
Not regulated as dangerous g	oods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	This substance/mixture is not intended to be transported in bulk.
15. Regulatory information	า
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export	Notification (40 CFR 707, Subpt. D)
	d Substances (29 CFR 1910.1001-1050)
Not listed. CERCLA Hazardous Substa Not listed.	nce List (40 CFR 302.4)
	authorization Act of 1986 (SARA)
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No
SARA 302 Extremely hazard	Reactivity Hazard - No lous substance
Not listed.	
SARA 311/312 Hazardous chemical	Yes
SARA 313 (TRI reporting) Not regulated.	
Other federal regulations	
	112 Hazardous Air Pollutants (HAPs) List
	112(r) Accidental Release Prevention (40 CFR 68.130)
Not regulated. Safe Drinking Water Act (SDWA)	Not regulated.
US state regulations	WARNING: This product contains a chemical known to the State of California to cause cancer.
US. Massachusetts RTM	
Portland Cement (CA Silica Sand (CAS 14	
Calcium sulfate, anh Portland Cement (CA Silica Sand (CAS 14)	

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate, anhydrous (CAS 14798-04-0) Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. Rhode Island RTK Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Silica Sand (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-March-2015
Revision date	-
Version #	01
NFPA ratings	200
References	HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)
Disclaimer	The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.