

# SOPRASEAL®

## LT ADDITIVE

SOPRASEAL®  
LT ADDITIVE  
PRODUCT # A503

## PRODUCT DATA SHEET

### DESCRIPTION & FEATURES

SOPRASEAL LT Additive is a liquid additive designed to be combined with SOPRASEAL LM 202 VP and SOPRASEAL LM 203. When blended with one of these products, it allows for application at temperatures as low as 25°F (-4°C).

### STORAGE

Store unopened containers in a clean dry location and cover as necessary to protect product from environmental damage such as freezing temperatures, extreme heat and direct sunlight. The shelf life of SOPRASEAL LT Additive is approximately 24 months from the original date of manufacture when stored as recommended.

### APPLICATION

Prior to installation, ensure that the substrate is free of frost and condensation. Follow all application instructions for SOPRASEAL LM 202 VP and SOPRASEAL LM 203. SOPRASEAL LT Additive can be applied in temperatures as low as 25°F (-4°C) without the use of additional heat. SOPRASEAL LT Additive must be protected from precipitation for a minimum of 24 hours and temperatures must remain at or above 25°F (-4°C) until the material has dried. Drying time varies depending on ambient and substrate temperatures, humidity, and the ability of the substrate to absorb water.



#### QUICK FACTS

LOW TEMP USE (°F)	BOTTLE SIZE (QT)	BOTTLES/ CARTON
25 (-4°C)	1 (0.95 L)	8



[www.soprema.us](http://www.soprema.us)  
310 Quadral Drive, Wadsworth, Ohio 44281  
Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10310 - REV. 031816