

SOPRASEAL® MESH

SOPRASEAL Mesh is a reinforced non-woven polyester fabric designed to be installed at joints, openings and details. SOPRASEAL Mesh can be used with SOPRASEAL LM 202 VP and SOPRASEAL LM 203.

INSTALLATION

SOPRASEAL Mesh is imbedded in a skim coat of SOPRASEAL LM 202 VP or SOPRASEAL LM 203 and then coated with a field layer.

SOPRASEAL MESH

PRODUCT CODE

A505

Scan QR code with the SOPREMA toolbox app for more information.



SOPRASEAL® SEALANT

SOPRASEAL Sealant is a low VOC, solvent-free, polyether adhesive-sealant. This fast-setting, moisture curing product is designed to be applied where outgassing and solvents are not tolerated. SOPRASEAL Sealant's tough elastomeric bonds allow for excellent adhesion to most construction materials as well as all SOPRASEAL membranes. SOPRASEAL Sealant can be applied at temperatures as low as 32°F (0°C) with a pneumatic cartridge (no special tools or mixers required). SOPRASEAL Sealant will not shrink upon curing or dissolve when left exposed to UV. SOPRASEAL is fast setting and after 24 hours is fully cured.

INSTALLATION

Ensure application surface is clean, sound, dry and free of debris. Test substrate prior for bonding strength and compatibility prior to application. SOPRASEAL Sealant is used as an accessory sealant to all SOPREMA wall membranes.

SOPRASEAL SEALANT

PRODUCT CODE

D30177

Scan QR code with the SOPREMA toolbox app for more information.

