

Henry® commercial air barrier systems selection chart

	Primary air barrier membranes										Flashings					Sealants			Primers			
	Fluid applied					Self-adhered																
	Air-Bloc® All Weather STPE™ ³	Air-Bloc® 16MR	Air-Bloc® 17MR	Air-Bloc® 21	Blueskin® VP160	Blueskin® SA	Blueskin® SA LT	Foilskin®	Blueskin® Metal Clad®		Air-Bloc® LF	Blueskin® Butyl Flash	Blueskin® TWF	Blueskin® SA	Blueskin® SA LT	Kop-R-Lastic® Metal Clad®	925 BES Sealant	Blueskin® Sealant	Blueskin® Adhesive	Blueskin® LVC Adhesive	Aquatac™ Spray Prep Adhesive	Hi-Tac™ Primer
Vapour permeable	•	•	•	•						•							•	•	•	•	•	
Vapour impermeable		•	•			•	•	•	•		•	•	•	•	•	•	•					
Permanent UV exposure <i>Under open joint cladding</i>	•						•	•						•								
Low application temperature <i>Lower than 4 °C (40 °F)</i>	•	•	•	•	• ¹		• ¹			•	•	•		• ¹		•	•	•	•	•	•	•
Low VOC ² <i>100 g limit</i>	•	•	•		n/a	n/a	n/a	n/a	n/a	•	n/a	n/a	n/a	n/a	n/a	•					•	
Self-gasketing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					
Mould resistant	•	•	•		n/a	n/a	n/a		n/a	•	n/a	n/a	n/a	n/a	n/a							

1. Primer required 2. VOC regulations do not apply to articles such as sheet applied membranes and flashings. VOCs are only measured in certain liquid products.
3. Passes AAMA 714-19. Can also be used as a liquid flashing when Air-Bloc All Weather STPE is the primary air barrier membrane. See Installation Manual and Technical Data Sheet for application details.

Air permeance and durability:
Low air permeance per ASTM E2178 and ASTM E2357. Meet CAN/ULC S741 and S742 air permeance and long-term durability standards.

Self-gasketing:
Meet ASTM D1970 and AAMA 711 for sealing around fasteners, eliminating water penetration even after the exterior facade is installed.

Sustainable and environmental design benefits:
Contribute to sustainable design, energy efficiency and LEED credits, by utilizing durable, low-VOC air barriers. Health Product Declarations and Red List status information are available for transparency.

Consult updated **Technical Data Sheet** for most recent information

Henry, Blueskin, Air-Bloc, Foilskin and Kop-R-Lastic are registered trademarks of the Henry Company.

Ask us today about other Henry® solutions that help manage the flow of water, air, vapour and energy.

Building Envelope Systems®
Roofing | Air Barrier | Waterproofing