THE RIGHT EQUIPMENT FOR THE JOB



High Quality Airless Fluid Hoses and Whip Hoses

			MAX. WORKING PRESSURE - PSI (MPa)					
		IGTH	3300 (22.8)	3600 (24.8)	4500 (31.0)	6500 (44.8)	7500 (51.7)	
I.D.	FEET	METERS	PART NO.	PART NO.	PART NO.	PART NO.	PART NO.	END CONNECTION
1/8"	3	0.9			290685			1/4" NPSM (F/M)
	3	0.9	291004					1/4" NPSM (F/M)
	5	1.5	316-506					1/4" NPSM (F/M)
3/16"	9	2.7	550-222					1/4" NPSM (F/M)
	25	7.6	291007					1/4" NPSM (FBE)
	50	15.2	291008					1/4" NPSM (FBE)
	3	0.9			2389428	2389440	2389450	1/4" NPSM (FBE)
	6	1.8	316-533*		2389430	2389442	2389452	1/4" NPSM (FBE)
	6	1.8	550-227					1/4" NPSM (FBE)
1/4"	12	3.7	2408659					1/4" NPSM (FBE)
	25	7.6	316-513					1/4" NPSM (FBE)
	50	15.2	316-505	286498	2389429	2389441	2389451	1/4" NPSM (FBE)
	100	30.5			2389427	2389439	2389449	1/4" NPSM (FBE)
	6	1.8			2389436	2389446	2389456	3/8" NPSM (FBE)
3/8"	25	7.6	508342					3/8" NPSM (FBE)
3/8	50	15.2	291006	286499	2389434	2389445	2389455	3/8" NPSM (FBE)
	100	30.5			2389432	2389444	2389453	3/8" NPSM (FBE)
	25	7.6	225-112*					1/2" NPSM (FBE)
1/2"	50	15.2	250-112*		2389425	2389438	2389448	1/2" NPSM (FBE)
	100	30.5			2389424	2389437	2389447	1/2" NPSM (FBE)
3/4"	50	15.2				2389443		3/4" NPSM (FBE)

^{*}Textile Braid. Spring guards at both ends.

Moisture Resistant Hose

DESCRIPTION	PART NO.
3/8" x 7500 PSI x 50'	375750050ML
1/2" x 7500 PSI x 50'	500750050ML
3/4" x 1000 PSI Transfer hose	750100012R



FBE Female Both Ends, NPT National Pipe Tapered Thread, NPSM National Pipe Straight Mechanical Thread, MBE Male Both Ends, F/M 1 Female / 1 Male Connection