

Revision Number: 004.0 Issue date: 10/08/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI VP275 Multipurpose Silicone IDH number: 1493958

Sealant

Product type: Silicone Item number: 1493958 Restriction of Use: None identified Region: United States

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Contact information: Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
WARNING:	MAY CAUSE AN ALLERGIC SKIN REACTION.		

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Contaminated w ork clothing should not be allow ed out

of the workplace. Wear protective gloves.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Response:

Wash contaminated clothing before reuse.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Silica	7631-86-9	5 - 10	
Oximino silane	Proprietary	1 - 5	
Oximino silane	Proprietary	0.1 - 1	
Silane derivative	Proprietary	0.1 - 1	

IDH number: 1493958 Product name: OSI VP275 Multipurpose Silicone Sealant * Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water. If

symptoms develop and persist, get medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If symptoms develop and persist, get medical attention.

Ingestion: Do not induce vomiting. Get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray.

Hazardous combustion products: Oxides of carbon. Oxides of silicon. Oxides of nitrogen. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system.

Clean-up methods: Wear suitable protective clothing, gloves and eye/face protection. Scrape up

as much material as possible. Clean residue with soap and water. Wash aw ay residue with plenty of water. Spilled material will solidify. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls/

Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed fromhands. Residual sealant may transfer to lenses and cause eye irritation. Keep

container closed.

Storage: Keep in a cool, well ventilated area away fromheat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	osha pel	AIHA WEEL	OTHER
Silica	3 mg/m3 TWA Respirable fraction. 6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Oximino silane	None	None	None	None
Oximino silane	None	None	None	None
Silane derivative	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Safety showers and eye

wash stations should be available.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Clear Odor: Mild

Odor threshold: Not available. pH: Not available. Not available. Vapor pressure: Boiling point/range: Not available. Melting point/range: Not applicable Specific gravity: 1.04

Vapor density: Not available. Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flam mable/Explosive limits - low er: Not applicable Flam mable/Explosive limits - upper: Not applicable Autoignition temperature: Not applicable Flam mability: Not applicable Evaporation rate: Not applicable

Solubility in water: Not soluble. Polymerizes in presence of water.

Partition coefficient (n-octanol/water): Not available.

VOC content: < 3.00 %; 41 g/l EPA Method 24

Not available. Viscosity: Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Polymerization can occur.

Hazardous decomposition

Oxides of carbon. Oxides of silicon. Oxides of nitrogen. Formaldehyde. Methyl ethyl ketoxime products:

formed during cure. Contact with waterliberates methanol.

Incompatible materials: Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Avoid moisture. Store aw ay from incompatible materials.

IDH number: 1493958 Product name: OSI VP275 Multipurpose Silicone Sealant

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors from uncured sealant may cause respiratory tract irritation. When heated to

temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible

limit.

Skin contact: May cause skin irritation. May cause allergic skin reaction.

Eye contact: May cause eye irritation. Ingestion: May be harmful if sw allow ed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silica	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
Oximino silane	None	Irritant, Allergen
Oximino silane	None	Irritant, Allergen
Silane derivative	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silica	No	No	No
Oximino silane	No	No	No
Oximino silane	No	No	No
Silane derivative	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

Canada Regulatory Information

IDH number: 1493958

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/08/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: OSI VP275 Multipurpose Silicone Sealant