



**Extremely Flammable – Brush Grade**

**DAP® 0308 Premium Brush Grade High Heat Resistant Contact Adhesive**

Superior quality adhesive designed to allow maximum application of

adhesive with minimum strokes of brush or roller. DAP® 0308 Premium has developed a broad range of applications in industry. Dries rapidly with high strength and high heat resistance.

Case Code	Size	Color	Case Pack	Case Weight (lb)
00094	5 gal	NATURAL	1	36.75

**DAP® 2056 Professional Brush Grade Contact Adhesive**

A medium viscosity formulation which meets the requirements of many applications. A general purpose contact adhesive, DAP®

2056 Professional is often the choice of shops and tradesmen engaged in a variety of projects requiring contact adhesive. Easy to apply. Fast drying.

Case Code	Size	Color	Case Pack	Case Weight (lb)
00241	5 gal	NATURAL	1	35.00

**Extremely Flammable – Spray Grade**

**DAP® Landau Top & Trim High Heat Resistant Contact Cement**

The ideal contact cement for automotive interior applications.

Its high heat resistance is well suited for adhering headliners, fabric and many other materials during automobile refurbishment. Easy to apply with hot or cold spray equipment.

Case Code	Size	Color	Case Pack	Case Weight (lb)
00233	1 gal	NATURAL	4	29.50
00234	5 gal	NATURAL	1	36.00
00235	55 gal	NATURAL	1	400.00
00237	5 gal	RED	1	36.00

**DAP® Landau Top & Trim 1145 High Heat Resistant Contact Cement**

DAP's lower VOC, professional contact adhesive with high-bond strength that increases with

age Landau Top & Trim 1145's high solids, low solvent formula maintains excellent adhesion in high temperatures. Its enhanced formula is especially developed for interior automotive, marine & RV customization & refurbishment.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lb)
00250	5 gal	NATURAL		1	37.80

**DAP® 0306/0307 High Heat Resistant Contact Adhesive**

This industry standard, used with confidence for years, meets the

requirements of a wide range of applications. Features ease of use and excellent end results. May be applied with standard hot or cold spray equipment.

Case Code	Size	Color	Drum Type	Case Pack	Case Weight (lb)
00095	5 gal	NATURAL		1	37.00
00097	5 gal	RED		1	37.00
04051	55 gal	NATURAL	O.H.*	1	414.00
04054	55 gal	RED	O.H.*	1	424.00

Description		Solids (percent)	Viscosity, cPs	Density, lb/gal.	Color(s)	Sq. Ft. Coverage (2-3 g dry)	Shelf Life	VOC Less H-0/ Exempt g/L	Sizes (Gallons)	
<b>Brush Grade (Flammable Solvent)</b>										
0308	Premium	HHR*	24	900-1200	6.8	NATURAL	309	1 yr	592/475	5-55
2056	Prof.	HHR*	20	550-800	6.7	NATURAL	253	1 yr	606/490	5-55
<b>Spray Grade (Flammable Solvent)</b>										
0307	Std.	HHR*	19	130-200	6.6	RED	237	1 yr	621/499	5-55
0306	Std.	HHR*	19	130-200	6.6	NATURAL	237	1 yr	621/499	5-55
LANDAU	Std.	HHR*	19	130-200	6.6	RED	237	1 yr	621/499	1-5-55
1145	Std.	HHR,	24	400-450	7.8	NATURAL	237	1yr	540	5

\*(T.H.) Tight Head \*(O.H.) Open Head \*(HHR) High Heat Resistance

For more detailed information, request the technical data sheet for any of our products by calling 1-888-327-8477 or visit our website at [dap.com](http://dap.com)