

### Product and Supplier Names

Maxxon<sup>®</sup> Acousti-Top<sup>®</sup> Adhesive  
Maxxon Corporation  
920 Hamel Road · PO Box 253  
Hamel, MN 55340  
[www.Maxxon.com/123EZ](http://www.Maxxon.com/123EZ) · [info@maxxon.com](mailto:info@maxxon.com)  
800-238-8461

### Product Description/Use

Acousti-Top Adhesive is an acrylic copolymer used to bond Acousti-Top sound mat to concrete or gypsum subfloors.

#### FEATURES:

- Pressure sensitive adhesive
- Aggressive dry tack
- Excellent adhesion to difficult to bond substrates
- Good surface wet-out
- Exhibits early tack

### Packaging

Product Number .....13058  
Package Type .....Pail  
Package Size .....5 gal. (18.93 L)  
Coverage .....1,250 ft<sup>2</sup>/pail

### Technical Data

Nonvolatiles, %.....55.0 - 57.0  
pH..... 6.5 - 7.8  
Weight  
US lbs/gal ..... 8.5 - 8.7  
Kg/L ..... 1.0  
VOC Content..... 1 g/L

### Installation

TOOLS NEEDED: 1/4" nap roller, brush or spray tool

PREP: The substrate surface should be broom cleaned, contaminant free and should have a smooth finish free from voids and sharp protrusions. If Acousti-Top Adhesive is installed over a Maxxon Underlayment, the underlayment must be dry and sealed prior to adhesive application using Maxxon Gypsum Overspray.

Concrete substrate should be installed a minimum of 28 days prior to Acousti-Top installation or utilize a Maxxon-approved topical

moisture barrier. The concrete subfloor shall be tested on grade, below grade or elevated slabs for MVER (Moisture Vapor Emission Rate) as per ASTM F1869 (Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride) or RH (Relative Humidity) as per ASTM F2170 (Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs using In Situ Probes). If excessive moisture is present, corrective actions must be taken.

MIX RATIO: Do not dilute. Acousti-Top Adhesive is ready to use directly from the pail.

INSTALLATION: Roll (1/4" nap roller), brush or spray Acousti-Top Adhesive at a rate of 300 ft<sup>2</sup>/gal (7.4 m<sup>2</sup>/L). Apply the adhesive in 48" (122 cm) wide strips and place the Acousti-Top sound mat into the wet or tacky adhesive and dry roll with a standard resilient floor roller to insure 100% adhesive coverage below the mat. This will minimize working over the adhesive throughout the installation.

Floor goods may be installed direct to Acousti-Top sound mat.

### Storage and Disposal

Keep from freezing; do not store below 40 °F (5 °C). Keep container closed when not in use. Keep in a dry, cool place.

Dispose of waste by following federal, state and local regulations. If spill occurs, clean up with potable water.

### Warranty, Availability and Technical Services

See our website for complete warranty information. Technical performance verification and service is available through Maxxon Corporation or Maxxon Regional Representative throughout North America.