

BELOW GRADE & AIR & VAPOR BARRIERS

PROTECTO UNIVERSAL PRIMER-FREE MEMBRANE

This high performance thru-wall flashing tape is designed to be applied down to -20°F (-28°C) without the use of primer or mechanical fasteners on most substrates. It's also specifically designed for use as a thru-wall flashing, below grade waterproofing membrane, seals skirt board-foundation to wood frame interface, ICF waterproofing membrane and as an air and vapor barrier.

NEW

- No primer needed – utilizes Protecto Wrap's Primerless Super Stick Technology™
- Sticks down to -20°F (-28°C)
- Adheres to damp surfaces
- Compatible with and will adhere to most construction surfaces, wood, concrete, CMU block, OSB, plywood, glass mat exterior sheathing products, foam insulation board, ICF and metal
- 6 month exposure rating
- IAPMO ER #362 and "Class A" fire rating
- Roll sizes available: 4", 6", 9", 12", 18", 24", 36" x 50' • High temperature: 300°F



PW 100/40 (AIR VAPOR BARRIER)

A peel and stick membrane for use as a positive air/vapor stop in everyday construction. Our product is a 40 mil SBS modified rubberized asphalt sheet waterproofing membrane that fully bonds to most substrates through the primer course that has excellent conforming capabilities to irregular surfaces.

- Can be used for numerous applications such as:
 - Thru wall flashing
 - Full building wrap in envelope applications in cavity wall construction
 - Sealing window and door perimeters to the building substrates
 - Sealing around skylights
- Compatible with and will adhere to steel, wood, concrete, building paper, block wall, dry wall and insulation board
- IAPMO ER #362
- Roll sizes available: 6", 9", 12", 18", 24", 36" x 75' • High temperature: 240°F



PW 100/60 WATERPROOFING MEMBRANE

A peel and stick sheet of 60 mil thick SBS modified rubberized asphalt which is laminated on a heavy high-density polyethylene film on the outer face with a siliconized, release sheet on the adhesive side. Application areas include: foundation walls, ICF foundations and walls, tunnels, parking decks, etc.

- Consistent 60 mil thickness vs. liquid applied systems
- Durability for deep below grade use
- Peel and stick for quick and easy installation
- Roll sizes available: 36" x 67' • High temperature: 240°F



JIFFY SEAL® 140/60 WATERPROOFING MEMBRANE

A 60 mil, polyester internally reinforced, peel and stick sheet waterproofing membrane for use anywhere a positive waterproofing membrane may be needed. This membrane has a double silicone treated release film on the top that keeps the membrane from adhering to itself while on the roll.

- Double adhesive membrane allows drainage mat attachment without fasteners
- The only adhesive to adhesive seam overlap
- Ideal for use on foundation walls, decks, balconies, bathrooms, terraces, split slabs and parking structures
- Unique "zip strip" serration on both edges, allowing an adhesive-to-adhesive lap bond between each sheet for instant bonding
- Can be covered or backfilled immediately
- Can be installed horizontally or vertically
- Roll sizes available: 6", 9", 12", 18", 30", 36" x 50'

