

**DESCRIPTION**

**Available in both flat and tapered panels.** Closed-cell polyisocyanurate (polyiso) foam core integrally bonded to inorganic coated glass facers (CGF) on both sides. ACFoam®-III is offered in a variety of thicknesses (including tapered insulation), providing long-term thermal resistance (LTTR) values from 5.7 (4.3 for tapered) to 26.8. Flat ACFoam-III is available in 4ft x 8ft (1220mm x 2440mm) and 4ft x 4ft (1220mm x 1220mm) panels. Tapered ACFoam-III is available in 4ft x 4ft (1220mm x 1220mm) panels. Manufactured in accordance with **ASTM C1289, Type II, Class 2, Grade 2 (20 psi) or Grade 3 (25 psi) and CAN/ULC-S704 Type 2, Class 3 or Type 3, Class 3.**

**APPLICATIONS**

Manufactured and tested for use in new and re-roofing applications. ACFoam-III roof insulation shall be installed over the roof deck. ACFoam-III is used in built-up (BUR), modified bitumen, standing seam metal, ballasted single-ply, mechanically attached single-ply and adhered single-ply roofing systems. These roofing systems depend on proper installation for successful performance. Refer to roof cover manufacturer, FM Approvals® RoofNav and UL Product iQ® for additional application details.

**INSTALLATION**

ACFoam-III shall be kept dry before, during and after installation. This product will burn if exposed to an ignition source of sufficient heat and intensity. Do not apply flame directly to ACFoam-III insulation. Refer to product packaging, Atlas Technical Bulletin #12 and PIMA Technical Bulletin #109 for storage and handling recommendations. To minimize the effect of thermal bridging, and the impact of moisture/airflow into the roof system, Atlas strongly recommends the ACFoam-III be installed in multiple layers. Please reference the ACFoam Fastening Pattern Guide for General Installation, Usage Instructions, and Warranty information for ACFoam products. Typical field fastening requirements can be obtained from roof cover manufacturer and/or, FM Approvals Roof Nav, or FM Global Property Loss Prevention Data Sheet 1-29.

Prior to installation, Atlas Roofing Corporation recommends, as applicable, you consult with your local building code official(s), contract documents, design professional, and all other relevant parties to ensure appropriate compliance.

**PHYSICAL PROPERTIES**

ACFOAM-III MEETS OR EXCEEDS THE FOLLOWING PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	ASTM C1289 OR CAN/ULC S704 (MIN REQUIREMENTS)
DIMENSIONAL STABILITY	ASTM D2126	<2%
COMPRESSIVE STRENGTH	ASTM D1621	20 psi (140 kPa) or 25 psi (172 kPa)
WATER ABSORPTION	ASTM C209	<1.5%
	ASTM C1763	<1.5%
	ASTM D2842	<3.5%
WATER VAPOR TRANSMISSION	ASTM E96	<4.0 perm (228.8ng/(Pa*s*m²))
PRODUCT DENSITY	ASTM D1622	Nominal 2.0 pcf (32.04 kg/m³)
FLAME SPREAD	ASTM E84/UL723	40-60
SMOKE DEVELOPMENT	ASTM E84/UL723	50-170
TENSILE STRENGTH	ASTM D1623	>730 psf (35 kPa)
SERVICE TEMPERATURE	-	-100° to +250°F

\*Numerical ratings are not intended to reflect performance under actual fire conditions. Flame spread index of ≤75 and smoke development ≤450 meet code requirements for foam plastic roof insulation. Physical properties listed above are presented as typical average values as determined by referenced ASTM test methods and are subject to nominal manufacturing variations.

**CODE COMPLIANCE**

- **ASTM C1289 Type II, Class 2, Grade 2 (20 psi) or Grade 3 (25 psi)**
- **CAN/ULC-S704, Type 2, Class 3 or Type 3, Class 3**
- **CCMC No. 12423-L**
- **UL Certified for Canada – Insulated Roof Deck Assemblies** Construction No. C38 and 52. Meet CAN/ULC-S126, CAN/ULC-S101 and CAN/ULC-S107
- **UL 1256 Classification** Construction No. 120, 123 & 292
- **UL 790 (ASTM E108)** Roofing Systems Classification
- **UL 263 (ASTM E119)** Fire Resistance Classification
- **FM 4450/4470** Refer to FM Approvals® RoofNav for Specific System Details
- **IBC Chapter 26 & NBC** Sections on Foam Insulation
- **California State Thermal Insulation Directory**, T 1231
- **Miami-Dade**, NOA No. 17-1211.05
- **Florida Product Approval**, No. FL17989
- **GREENGUARD GOLD Certified**
- **UL 2824** Resistant to Mold Growth as Validated by UL Environment

**FLAT CGF ROOF INSULATION**

THICKNESS	THERMAL RESISTANCE		PIECES PER UNIT	SQUARE FEET PER UNIT		TRUCKLOAD QUANTITIES (SQUARES)	AVERAGE WEIGHT (LB/SF)	RECYCLED CONTENT		
	AVERAGE 'LTR VALUE	<sup>2</sup> RSI		4x8	4x4			POST CONSUMER	PRE CONSUMER	TOTAL
1.0"	5.7	1.00	48	1536	768	368.64	0.315	-	6.2%	6.2%
1.5"	8.6	1.50	32	1024	512	245.76	0.383	-	7.7%	7.7%
2.0"	11.4	2.01	24	768	384	184.32	0.450	-	8.7%	8.7%
2.5"	14.4	2.53	19	608	304	145.92	0.518	-	9.4%	9.4%
3.0"	17.4	3.06	16	512	256	122.88	0.585	-	10.0%	10.0%
3.5"	20.5	3.60	13	416	208	99.84	0.653	-	10.5%	10.5%
4.0"	23.6	4.15	12	384	192	92.16	0.720	-	10.9%	10.9%

**TAPERED CGF ROOF INSULATION**

SLOPE	LABEL	THICKNESS			THERMAL RESISTANCE		BOARD FT PER PIECE	PIECES PER UNIT	BOARD FT PER UNIT	SQUARE FT PER UNIT	WEIGHT (LB/SF)	RECYCLED CONTENT		
		MINIMUM	MAXIMUM	AVERAGE	AVERAGE 'LTR VALUE	<sup>2</sup> RSI						POST CONSUMER	PRE CONSUMER	TOTAL
1/8"	AA	0.5"	1.0"	0.75"	4.3	0.76	12	64	768	1024	0.281	-	5.2%	5.2%
1/8"	A	1.0"	1.5"	1.25"	7.1	1.25	20	38	760	608	0.349	-	7.0%	7.0%
1/8"	B	1.5"	2.0"	1.75"	10.0	1.76	28	26	728	416	0.416	-	8.2%	8.2%
1/8"	C	2.0"	2.5"	2.25"	12.9	2.27	36	20	720	320	0.484	-	9.1%	9.1%
1/4"	X	0.5"	1.5"	1.0"	5.7	1.00	16	48	768	768	0.315	-	6.20%	6.20%
1/4"	Y	1.5"	2.5"	2.0"	11.4	2.01	32	24	768	384	0.450	-	8.68%	8.68%
1/2"	Q	0.5"	2.5"	1.5"	8.6	1.51	24	32	768	512	0.383	-	7.66%	7.66%

<sup>1</sup>LTR (long term thermal resistance) values were determined in accordance with CAN/ULC-S770. Test samples were third-party selected and tested by an accredited material testing laboratory.

<sup>2</sup>RSI is the metric expression of R-value (m<sup>2</sup> • K/W).

*To minimize the effects of thermal bridging, and the impact of moisture/airflow into the roof system, Atlas strongly recommends the ACFoam insulation assembly be installed in multiple layers.*

**FOR A COMPLETE LIST OF PRODUCT SIZES, SCAN OR CLICK QR CODE TO DOWNLOAD THE PACKAGE & LOADING GUIDE**



**WARRANTY**

ACFoam-III is backed by a Limited 20-Year Thermal Warranty. For complete terms and conditions, visit [roof.atlasrwi.com/warranty](http://roof.atlasrwi.com/warranty)

Other than the aforementioned representations and descriptions, Atlas Roofing Corporation (hereafter, "Seller") makes no other representations or warranties as to the insulation sold herein. The Seller disclaims all other warranties, express or implied, including the warranty of merchantability and the warranty of fitness for a particular purpose. Seller does, however, have a limited warranty as to the LTR-Value of the insulation, the terms of which are available upon request from the Seller. Seller shall not be liable for any incidental or consequential damages including but not limited to the cost of installation, removal, repair or replacement of this product. Buyer's remedies shall be limited exclusively to, at Seller's option, the repayment of the purchase price or resupply of product manufactured by Atlas in a quantity equal to that of the nonconforming product. Atlas distributors, agents, salespersons or other independent representatives have no authority to waive or alter the above limitation of liability and remedies.



**Atlas Roofing Corporation**  
 2000 Riveredge Parkway, Suite 800 • Atlanta, GA • 30328  
 770-952-1442 • [roof.atlasrwi.com](http://roof.atlasrwi.com)

