

Revision Date: 11/08/2019

# SAFETY DATA SHEET

# 1. Identification

Material name: EUCOLASTIC 1SL GRAY - 12/30oz CS

Material: 174C 96

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

**EUCLID CHEMICAL COMPANY** 19218 REDWOOD ROAD **CLEVELAND OH 44110** US

Contact person: **EH&S** Department Telephone: 216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### **Hazard Classification**

## **Health Hazards**

Respiratory sensitizer Category 1 Skin sensitizer Category 1 Carcinogenicity Category 1A

## **Unknown toxicity - Health**

Acute toxicity, oral 57.25 % Acute toxicity, dermal 62.57 % 98.13 % Acute toxicity, inhalation, vapor Acute toxicity, inhalation, dust 90.48 %

or mist

# **Environmental Hazards**

Acute hazards to the aquatic Category 3 environment

# **Unknown toxicity - Environment**

Acute hazards to the aquatic 91.14 % environment

Chronic hazards to the aquatic

98.14 %

environment

### **Label Elements**



Revision Date: 11/08/2019

## **Hazard Symbol:**



Signal Word: Danger

Hazard Statement: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Harmful to aquatic life.

Precautionary Statements

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate

ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required. Avoid release

to the environment.

**Response:** IF INHALED: If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with

plenty of water/... If skin irritation or rash occurs: Get medical

advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before

reuse.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
-------------------	------------	-------------------------

Revision Date: 11/08/2019

Calcium Carbonate (Limestone)	1317-65-3	10 - <20%
Polyvinyl chloride	9002-86-2	10 - <20%
Petroleum distillates	64742-47-8	1 - <5%
Aliphatic naphtha	64742-88-7	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Xylene	1330-20-7	1 - <5%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Nonane	111-84-2	0.1 - <1%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Aluminum oxide	1344-28-1	0.1 - <1%
Decanedioic acid ester	52829-07-9	0.1 - <1%
lodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

# Description of necessary first-aid measures

Inhalation: Call a physician or poison control center immediately. If breathing

stops, provide artificial respiration. Move to fresh air. If breathing is

difficult, give oxygen.

**Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or

thoroughly clean contaminated shoes. Immediately remove

contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get

medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately

with water. If easy to do, remove contact lenses. If eye irritation

persists: Get medical advice/attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for First-

aid Responders:

Self-contained breathing apparatus and full protective clothing must

be worn in case of fire.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

# 5. Fire-fighting measures



Revision Date: 11/08/2019

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

## 6. Accidental release measures

Personal precautions,

protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment, Keep upwind, Keep unauthorized personnel away. Do not touch damaged containers or spilled

material unless wearing appropriate protective clothing.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Methods and material for containment and cleaning

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

**Environmental Precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe

to do so.

## 7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Safe handling advice: Ventilate well, avoid breathing vapors. Use approved respirator if air

> contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and

clothing. Wash hands thoroughly after handling.



Revision Date: 11/08/2019

Contact avoidance measures: No data available.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

Storage

Safe storage conditions: Store locked up.

Safe packaging materials: No data available.

# 8. Exposure controls/personal protection

# **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	<b>Exposure Limit Values</b>	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/	g/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/	Contaminants (29 CFR 1910.1000), as amended (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/	amended (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (02 2006)
	OSHA_AC T	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/	Contaminants (29 CFR 1910.1000), as amended (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/	Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	50 million: particles cubic foc	s per amended (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 million particles cubic foc	us. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/	g/m3 US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/	g/m3 US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Petroleum distillates - Non- aerosol as total hydrocarbon vapor	TWA	200 mg/	g/m3 US. ACGIH Threshold Limit Values, as amended (2011)
·	TWA	200 mg/	g/m3 US. ACGIH Threshold Limit Values, as amended (2011)
Aliphatic naphtha - Non- aerosol as total hydrocarbon vapor	TWA	200 mg/	g/m3 US. ACGIH Threshold Limit Values, as amended (03 2014)
Aliphatic naphtha	PEL	100 ppm 400 mg/	g/m3 US. OSHA Table Z-1 Limits for Air



**EUCLID CHEMICAL** 

Version: 2.2

				Contaminants (29 CFR 1910.1000), as amended (01 2017)
Titanium dioxide	TWA		10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Titanium dioxide - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide - Respirable fraction.	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Calcium oxide	TWA		2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL REL	150 ppm 100 ppm	655 mg/m3 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)  US. NIOSH: Pocket Guide to Chemical
	STEL	150 ppm	655 mg/m3	Hazards, as amended (2010)  US. NIOSH: Pocket Guide to Chemical
	REL	100 ppm	435 mg/m3	Hazards, as amended (2010) US. NIOSH: Pocket Guide to Chemical
	STEL	150 ppm	655 mg/m3	Hazards, as amended (2010)  US. OSHA Table Z-1-A (29 CFR 1910.1000),
	TWA	100 ppm	435 mg/m3	as amended (1989) US. OSHA Table Z-1-A (29 CFR 1910.1000),
	TWA	100 ppm	435 mg/m3	as amended (1989)  US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	AN ESL		180 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2011)





PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000), as amended (02 2006)
TWA	0.005 ppm		US. ACGIH Threshold Limit Values, as
T\A/A	20 nnm		amended (2011) US. ACGIH Threshold Limit Values, as
IVVA	20 ppm		amended (2011)
PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as
			amended (03 2014)
PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air
	• •		Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000), as amended (02 2006)
Τ\Λ/Δ	200 nnm		US. ACGIH Threshold Limit Values, as
1 ***	200 ppm		amended (02 2012)
TWA		1 mg/m3	US. ACGIH Threshold Limit Values, as
			amended (2011)
PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000), as amended (02 2006)
PFI		15 mg/m3	US. OSHA Table Z-1 Limits for Air
		. cgc	Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
TWA		50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
			amended (03 2016)
TWA			US. OSHA Table Z-3 (29 CFR 1910.1000), as
		particles per	amended (03 2016)
		cubic foot of	,
		air	
TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
Τ\Λ/Δ		15 mg/m3	amended (03 2016) US. OSHA Table Z-3 (29 CFR 1910.1000), as
1 * * * ^ _		15 mg/ms	amended (03 2016)
	TWA TWA PEL TWA PEL TWA TWA TWA PEL TWA TWA PEL	TWA 0.005 ppm TWA 20 ppm PEL 100 ppm TWA PEL 500 ppm PEL TWA 200 ppm TWA PEL TWA TWA TWA TWA	TWA         0.005 ppm           TWA         20 ppm           PEL         100 ppm         435 mg/m3           TWA         5 mg/m3           PEL         500 ppm         2,000 mg/m3           PEL         5 mg/m3           TWA         200 ppm           TWA         1 mg/m3           PEL         5 mg/m3           TWA         50 millions of particles per cubic foot of air           TWA         15 mg/m3           TWA         5 mg/m3

Chemical name	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 m	g/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 m	g/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 m	g/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 m	g/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 m	g/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Petroleum distillates - Non- aerosol as total hydrocarbon vapor	TWA	200 m	g/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 m	g/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Petroleum distillates - Non- aerosol as total hydrocarbon vapor	TWA	200 m	g/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	200 m	g/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 m	g/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 m	g/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 m	g/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 m	g/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Calcium oxide	TWA	2 m	g/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 m	g/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Calcium oxide	TWA	2 m	g/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Xylene	TWA	100 ppm 434 m	g/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm 651 m	g/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation



**EUCLID CHEMICAL** 

Version: 2.2

				296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)



Chemical name	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Petroleum distillates - Non- aerosol as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Petroleum distillates - Non- aerosol as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)



Aliphatic naphtha - Non- aerosol as total hydrocarbon vapor	TWA		200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aliphatic naphtha - Non- aerosol as total hydrocarbon vapor	TWA		200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aliphatic naphtha	TWA	400 ppm	1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation



				296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)



l	1	1	1
Nonane	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Nonane	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Nonane	TWA	200 ppm 1,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)



Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational
				Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Toluene	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Iron oxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust as Fe	TWA		5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	STEL		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	TWA		5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Iron oxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Iron oxide - Dust and fume as Fe	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)



Benzene	TWA	1 ppm	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	5 ppm	15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Naphthalene	STEL	15 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Naphthalene	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Naphthalene	TWA	10 ppm	52 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	15 ppm	79 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Methanol	STEL	250 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methanol	STEL	250 ppm	328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	200 ppm	262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)



Revision Date: 11/08/2019

Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Phenol	TWA	5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Phenol	TWA	5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Phenol	TWA	5 ppm	19 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA		5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Vinyl chloride	TWA	1 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Vinyl chloride	TWA	1 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Vinyl chloride	TWA	1 ppm	2.6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

**Biological Limit Values** 

9.00.00				
Chemical Identity	Exposure Limit Values	Source		
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)		
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)		

**Exposure guidelines** 

Petroleum distillates	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.



Revision Date: 11/08/2019

Aliphatic naphtha	US. ACGIH Threshold Limit Values, as	Can be absorbed through	
	amended	the skin.	

**Appropriate Engineering** 

Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

**General information:** Use personal protective equipment as required.

**Eye/face protection:** Wear goggles/face shield.

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

#### 9. Physical and chemical properties

## **Appearance**

Physical state: solid
Form: Paste
Color: Gray
Odor: Mild

Odor threshold:

pH:

No data available.

Flash Point: > 93 °C > 199 °F(Setaflash Closed Cup)

**Evaporation rate:** Slower than n-Butyl Acetate

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.



Revision Date: 11/08/2019

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.32

Solubility(ies)

Solubility in water: Insoluble in water
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

## 10. Stability and reactivity

Reactivity: No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g.

nitric acid, peroxides and chromates). Strong bases. Water, moisture.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

## 11. Toxicological information

## Information on likely routes of exposure

**In high concentrations**, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** Causes mild skin irritation. May cause an allergic skin reaction.

**Eye contact:** Eye contact is possible and should be avoided.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

## Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.



Revision Date: 11/08/2019

## Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

Petroleum distillates LD 50 (Rat): > 5,000 mg/kg

Aliphatic naphtha LD 50 (Rat): > 5,000 mg/kg

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Hydrotreated heavy naphthenic distillate

LD 50 (Rat): > 5,000 mg/kg

Nonane LD 50 (Rat): > 5,000 mg/kg

Diisodecyl phthalate LD 50 (Rat): 64,000 mg/kg

Aluminum oxide LD 50 (Rat): > 10,000 mg/kg

Decanedioic acid ester LD 50 (Rat): 3,700 mg/kg

lodopropynyl butylcarbamate LD 50 (Rat): 1.1 g/kg

Dermal

**Product:** Not classified for acute toxicity based on available data.



Revision Date: 11/08/2019

Specified substance(s):

Petroleum distillates LD 50 (Rabbit): > 2,000 mg/kg

Aliphatic naphtha LD 50 (Rabbit): > 2,000 mg/kg

**Xylene** LD 50 (Rabbit): 12,126 mg/kg

Isophorone Diisocyanate LD 50 (Rat): > 7,000 mg/kg

Ethylbenzene LD 50 (Rabbit): 17,800 mg/kg

Hydrotreated heavy naphthenic distillate

LD 50 (Rabbit): > 5,000 mg/kg

Nonane LD 50 (Rabbit): > 2,000 mg/kg

Diisodecyl phthalate LD 50 (Rabbit): > 3,160 mg/kg

Decanedioic acid ester LD 50 (Rat): > 3,170 mg/kg

lodopropynyl butylcarbamate

LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

**Product:** ATEmix: 9.72 mg/l

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):



Revision Date: 11/08/2019

Petroleum distillates in vivo (Rabbit): Irritating

Aliphatic naphtha in vivo (Rabbit): Irritating

Titanium dioxide in vivo (Rabbit): Not irritant

Xylene in vivo (Rabbit): Moderate irritant

Hydrotreated heavy

naphthenic distillate

in vivo (Rabbit): Not irritant

Nonane in vivo (Rabbit): Irritating

Aluminum oxide in vivo (Rabbit): Not irritant

Decanedioic acid ester in vivo (Rabbit): Not irritant

# Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Petroleum distillates Rabbit, 24 - 72 hrs: Not irritating

Aliphatic naphtha Rabbit, 24 - 72 hrs: Not irritating

Titanium dioxide Rabbit, 24 hrs: Not irritating

Xylene Rabbit, 24 hrs: Moderately irritating

Ethylbenzene Rabbit, 7 d: Slightly irritating

Hydrotreated heavy

naphthenic distillate

Rabbit, 24 hrs: Not irritating

Nonane Rabbit, 24 - 72 hrs: Not irritating

Aluminum oxide Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization

**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

**Product:** No data available.



Revision Date: 11/08/2019

## IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

naphthenic distillate evaluation: Carcinogenic to humans.

#### **US. National Toxicology Program (NTP) Report on Carcinogens:**

Hydrotreated heavy Known To Be Human Carcinogen.

naphthenic distillate

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

#### **Germ Cell Mutagenicity**

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specific Target Organ Toxicity - Repeated Exposure

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

# 12. Ecological information

#### **Ecotoxicity:**

## Acute hazards to the aquatic environment:



Revision Date: 11/08/2019

Fish

**Product:** No data available.

Specified substance(s):

Petroleum distillates LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 2.9

mg/l Mortality

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Ethylbenzene LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2

mg/l Mortality

Diisodecyl phthalate LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality

lodopropynyl LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 -

butylcarbamate 0.089 mg/l Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Diisodecyl phthalate EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Aliphatic naphtha NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/l QSAR QSAR, Key study

Hydrotreated heavy NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR,

naphthenic distillate Supporting study

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

**Persistence and Degradability** 

Biodegradation

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.



Revision Date: 11/08/2019

Bioaccumulative potential

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Nonane Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

# 13. Disposal considerations

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

# 14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

# 15. Regulatory information

## **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.



Revision Date: 11/08/2019

# US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u> <u>OSHA hazard(s)</u>

Polyvinyl chloride Blood Liver

Cancer Flammability

Central nervous system

Benzene Blood

respiratory tract irritation Central nervous system

Flammability Cancer Skin Aspiration Eye

Crystalline Silica kidney effects (Quartz)/ Silica Sand lung effects

immune system effects

Cancer

Vinyl chloride Blood

Liver

Flammability

Central nervous system

Cancer

## CERCLA Hazardous Substance List (40 CFR 302.4):

**Chemical Identity** Reportable quantity 100 lbs. Xylene Ethylbenzene 1000 lbs. Nonane 100 lbs. Toluene 1000 lbs. Benzene 10 lbs. Naphthalene 100 lbs. 5000 lbs. Cumene Methanol 5000 lbs. Phenol 1000 lbs. Vinyl chloride 1 lbs.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **Hazard categories**

Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards Respiratory or Skin Sensitization

Carcinogenicity



Revision Date: 11/08/2019

## **SARA 302 Extremely Hazardous Substance**

Reportable

<u>Chemical Identity</u> <u>quantity</u> <u>Threshold Planning Quantity</u>

Isophorone Diisocyanate 500 lbs. 500 lbs. Phenol 1000 lbs. 500 lbs.

## SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Xylene 100 lbs.

Isophorone Diisocyanate

Ethylbenzene 1000 lbs. Nonane 1000 lbs.

Diisodecyl phthalate

Toluene 1000 lbs.
Benzene 10 lbs.
Naphthalene 100 lbs.
Cumene 5000 lbs.
Methanol 5000 lbs.

Diisodecyl phthalate

(mixed Is)

Phenol 1000 lbs. Vinyl chloride 1 lbs.

#### SARA 311/312 Hazardous Chemical

**Chemical Identity Threshold Planning Quantity** Isophorone Diisocyanate 500lbs Phenol 500lbs 10000 lbs Calcium Carbonate (Limestone) Polyvinyl chloride 10000 lbs Petroleum distillates 10000 lbs Aliphatic naphtha 10000 lbs 10000 lbs Titanium dioxide Calcium oxide 10000 lbs Xylene 10000 lbs Ethylbenzene 10000 lbs Hydrotreated heavy 10000 lbs naphthenic distillate Nonane 10000 lbs Diisodecvl phthalate 10000 lbs Aluminum oxide 10000 lbs Decanedioic acid ester 10000 lbs lodopropynyl 10000 lbs

## SARA 313 (TRI Reporting)

### **Chemical Identity**

butylcarbamate

Xylene

Ethylbenzene

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity Reportable quantity

Vinyl chloride lbs

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity Reportable quantity



Revision Date: 11/08/2019

**Xylene** 

Reportable quantity: lbs.

## **US State Regulations**

## **US. California Proposition 65**



#### **WARNING**

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

Calcium Carbonate (Limestone)

Polyvinyl chloride

Petroleum distillates

Aliphatic naphtha

Titanium dioxide

Calcium oxide

Xylene

Ethylbenzene

Hydrotreated heavy naphthenic distillate

## **US. Massachusetts RTK - Substance List**

#### **Chemical Identity**

Calcium Carbonate (Limestone)

Petroleum distillates

Aliphatic naphtha

Titanium dioxide

Xylene

Isophorone Diisocyanate

Benzene

Crystalline Silica (Quartz)/ Silica Sand

Phenol

# US. Pennsylvania RTK - Hazardous Substances

## **Chemical Identity**

Calcium Carbonate (Limestone)

Petroleum distillates

Aliphatic naphtha

Titanium dioxide

Calcium oxide Xylene

#### **US. Rhode Island RTK**

# **Chemical Identity**

Calcium Carbonate (Limestone)

Polyvinyl chloride

Petroleum distillates

Aliphatic naphtha

Titanium dioxide

**Xylene** 

## International regulations



Revision Date: 11/08/2019

# Montreal protocol

Not applicable

# Stockholm convention

Not applicable

## **Rotterdam convention**

Not applicable

# **Kyoto protocol**

Not applicable

VOC:

Regulatory VOC (less water and : 110 g/l exempt solvent)

VOC Method 310 : 8.37 %



Revision Date: 11/08/2019

**Inventory Status:** 

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Mexico INSQ: One or more components in this product are

not listed on or exempt from the Inventory.

Ontario Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this product are

not listed on or exempt from the inventory.



Revision Date: 11/08/2019

# 16.Other information, including date of preparation or last revision

**Revision Date:** 11/08/2019

Version #: 2.2

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.