



## COLPHENE 3000

COLPHENE 3000 is a self-adhered waterproofing membrane composed of a high quality elastomeric styrene-butadiene-styrene (SBS) polymer-modified bitumen blend and a polyethylene woven composite facer. COLPHENE 3000 is used for vertical and horizontal waterproofing of foundation walls, tunnels, plaza decks, parking decks and split slab construction. The underside consists of a release film and self-adhered bitumen layer for adhering to approved substrates.

**PRODUCT CODE:** D10209 (SUMMER) / D10211 (WINTER)

**DIMENSIONS:** 61.0 ft (18.7 m) x 39.4 in (1.0 m)

**THICKNESS:** 60 mils (1.5 mm)



## COLPHENE ICF

COLPHENE ICF is a self-adhered waterproofing membrane. COLPHENE ICF is composed of a high quality elastomeric styrene-butadiene-styrene (SBS) polymer-modified bitumen blend and a polyethylene woven composite facer. COLPHENE ICF is used for vertical and horizontal waterproofing of polystyrene (expanded or extruded) insulating concrete forms. The underside consists of a release film and self-adhesive bitumen layer for adhering to approved substrates.

**PRODUCT CODE:** D10126

**DIMENSIONS:** 75.0 (22.9 m) x 36.0 in (1.0 m)

**THICKNESS:** 40 mils (1.0 mm)



## COLPHENE SP 2.2

COLPHENE SP 2.2 is an SBS-modified bitumen base ply for use in approved multi-ply waterproofing assemblies. COLPHENE SP 2.2 is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with a high quality random glass fiber mat. The topside is surfaced with fine mineral aggregate and the underside is surfaced with polyolefin burn-off film to optimize heat welding.

**PRODUCT CODE:** 01218

**DIMENSIONS:** 49.2 ft (15.0 m) x 39.4 in (1.0m)

**THICKNESS:** 87 mils (2.2 mm)