

IMPACT 440

0.54 GPM

Recommended for small and medium residential and commercial projects.

Features:

Quad+ Packings

Sureflo™ Pusher Valve

Electronic Pressure Control with Rapid Clean

Faster flushing and clean-up.

AutoOiler™

Full-sized Manifold Filter

Filter handles more paint, preventing abrasives from reaching the gun tip.

PermaLife™ Cylinder

Will never wear out

Extra Deep Holster

Keeps strainer in liquid to keep pump moist.

(skid model only)



Impact 440

Step up to the #1 selling sprayer in the industry, the Impact 440! The Impact 440 is ideally suited for residential, property maintenance and small commercial applications. This high performance electric airless sprayer will apply all standard architectural primers, paints and coatings efficiently.

Impact 440	
SPECIFICATIONS	
Max. Delivery	0.54 GPM
Max. Tip Size	0.023"
Max. Operating Pressure	3300 PSI
Motor	7/8 HP, DCX Motor
WEIGHT	
Skid Frame	37 lbs.
High Rider	65 lbs.
Low Rider	57 lbs.
CONFIGURATIONS	PART NO.
Skid	805-000
High Rider	805-016
Low Rider	805-019



Impact® 440
High Rider



Impact® 440
Low Rider



The Impact 440 comes with RX-80 Gun, 517 TR¹ Reversible Tip and 1/4" x 50' Airless Hose.

THE CONTRACTOR CHOICE FOR ELECTRIC AIRLESS PAINT SPRAYERS



	Impact 410	Impact 440	Impact 540	Impact 640	Impact 740	Impact 840	Impact 1040	Impact 1040T	Impact 1140
Part Number - Skid	0532052	805-000	805-001	805-002	----	----	----	----	----
Part Number - High Rider	0532053	805-016	805-006	805-004	805-007	805-009	0552600	2405360	805-011
Part Number - Low Rider	----	805-019	805-003	805-005	805-008	805-010	----	----	805-012
Max Delivery (GPM)	0.47 (1.78 LPM)	0.54 (2.05 LPM)	0.60 (2.28 LPM)	0.70 (2.65 LPM)	0.80 (3.03 LPM)	1.00 (3.79 LPM)	1.15 (4.36 LPM)	1.50 (4.55 LPM)	1.20 (4.55 LPM)
Max Tip Size, 1-Gun	0.021"	0.023"	0.024"	0.027"	0.029"	0.032"	0.033"	0.033"	0.034"
Max Tip Size, 2-Guns	----	----	----	----	0.017"	0.021"	0.022"	0.022"	0.023"
Max Tip Size, 3-Guns	----	----	----	----	----	----	----	----	----
Max Tip Size, 4-Guns	----	----	----	----	----	----	----	----	----
Max. Operating Pressure (PSI)	3100 (21.4 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)	3300 (22.8 MPa)
Electric Motor	3/4 HP	7/8 HP, DCX	1.2 HP DuraLife Brushless HE DC	1.55 HP DuraLife Brushless HE DC	2.0 HP DuraLife Brushless HE DC	2.3 HP DuraLife Brushless HE DC	2.5 HP DuraLife Brushless HE DC	2.5 HP DuraLife Brushless 120V	2.6 HP DuraLife Brushless HE DC
Max. Hose Length	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)
Max. Cord Length	200' (60 m)	200' (60 m)	200' (60 m)	200' (60 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)	300' (90 m)
Power Cord Length - Skid	6' (2 m)	9' (3 m)	9' (3 m)	9' (3 m)	----	----	----	----	----
Power Cord Length - Cart	6' (2 m)	9' (3 m)	15' (5 m)	15' (5 m)	15' (5 m)	15' (5 m)	15' (5 m)	15' (5 m)	15' (5 m)
Tires - High Rider	10" Semi-pneumatic	10" Semi-pneumatic	10" Semi-pneumatic	10" Semi-pneumatic	10" Semi-pneumatic	12" Pneumatic	12" Pneumatic	12" Pneumatic	12" Pneumatic
Tires - Low Rider	----	8" Semi-pneumatic	8" Semi-pneumatic	8" Semi-pneumatic	10" Pneumatic	10" Pneumatic	----	----	10" Pneumatic
Weight - Skid (lbs)	34	42	42	42	----	----	----	----	----
Weight - Cart (lbs)	55	69	69	69	87	87	98	98	107
Gun Included	RX-80	RX-80	RX-Pro	RX-Pro	RX-Pro	RX-Pro	RX-Pro	RX-Apex (Non-filtered)	RX-Pro
Reversible Tip Included	517	517	517	517	517	517	517	517	517
Airless Hose Included	1/4" x 50'	1/4" x 50'	1/4" x 50'	1/4" x 50'	1/4" x 50'	1/4" x 50'	1/4" x 50'	3/8" x 50' & 1/4" x 6' Whip	1/4" x 50'
Repair Kit - Pump	704-586	704-586	704-586	704-586	805-1010	805-1010	0558740	0558740	0558740
Manifold Filter - Pump	581-059	730-067	730-067	730-067	730-067	730-067	730-067	730-067	730-067
Repair Kit - Gun	0538215	0538215	0538221	0538221	0538221	0538221	0538221	0538221	0538221